Installation Instructions
Water Filter Seal Replacement Kit
Part ASA34000

Instructions:

1. Turn water "OFF" to water filter. (Ball valve handles point across pipe).
2. If equipped, turn filter handle to the "OFF" position.
3. Place bucket under filter.
4. Remove sump and cartridge from filter housing.
5. If equipped, turn filter handle to the "ON" position and allow water lines to drain.
6. Loosen center screw from inside filter.
7. Disassemble filter head assembly as shown in diagram below.
8. Replace o-rings and gaskets. Note that female chamfer on gaskets face up.
9. Reassemble reverse of disassembly making sure that the handle "IN" and "OUT" markings match housing inlet and outlet ports.
10. **Valve test (If equipped with "ON" / "OFF" handle only)**
    - A) Place bucket under filter head.
    - B) Set filter handle to the "ON" position.
    - C) Slowly turn water "ON" to the filter.
    - D) Wait until water flows from divertor, then turn handle to the "OFF" position.
    - E) Check for leaks. (Slightly tighten divertor screw if necessary).
11. Reassemble sump and cartridge.
12. Re-establish water supply to water filter.
13. Check for leaks.

Apollo Dental Products, Inc. • 245 W. Dakota Ave. • Clovis, CA 93612 • Technical Support
559/292-1444 • 800/233-4151 • Fax 559/292-1555 • www.apollodental.com

AMI60785 Rev. 1/99